



JUMP STARTER SOS BOOSTER® MICRO 12V-700CA

APPLICATIONS



MOTOR		TYPE OF RECOVERY
Vehicle	12V	Normal conditions of use
Gasoline	✓	
Diesel	✓	



The correct use of a Ceteor Booster cannot cause any damage to the electronic of a vehicle..

Ceteor booster packs are perfectly compatible with hybrid vehicles.

TYPE OF VEHICLES TO BE JUMP STARTED
Car, 4Wd or commercial vehicle in good condition
New or second-hand motorbike
New or second-hand garden vehicle: garden tractors, etc.
New or second-hand leisure vehicles: ATV's, etc.

Diesel motors up to*:

POWER IN HP		
< 125	150	175
■ ■ ■	■	■
* Petrol motors are easier to start		

■ Normal






Following the principle "who can do more can do less" our most powerful battery boosters can also be convenient for the applications covered by less powerful battery boosters with same voltage of our range.

Caution :

The circumstances/conditions when starting a vehicle depend of various parameters: vehicle's condition, engine type (petrol or diesel) and power, presence of battery in vehicle or not, temperature, frequency of use ... Those influence the jump start's facility.

Chart for your information - Manufacturer's advice

TECHNICAL SPECIFICATIONS

Reference	861001
Voltage	12V
Cranking Amps	700 A
Peak Amps	1860 A
Nr of batteries	1
Starting cable length	1,30 m
Starting cable diameter	25 mm ²
Type of clamps	F600
Clamps length	160 mm
Clamps opening	40 mm
AC/DC* charger	1,3 A
Cable to charge DC/12V	
12V Output	16 A
Reverse polarity signal	
Internal fuse	300 A
Connector for auxiliary cables	
Net weight	9,5 kg
Dimensions (cm)	37,5 x 11 x 32
Gross weight	11,5 kg
Packing dimensions (cm)	38 x 14 x 44,5

-  Yes
-  No
-  Option
-  Upon request